

EAC326D-OD4Z

5MP HD Motorized VFEXIR Dome Camera



Key features

- 5megapixel high-performance CMOS
- HD analog output, up to 5 MP resolution
- 2.8 to 12mm motorized vari-focal lens
- OSD menu, DNR, Smart IR
- EXIR technology, up to 40m IR distance
- IP67
- Up the Coax

Specifications

EAC326D-OD4Z	
Camera	
Image Sensor	5 MP CMOS image sensor
Effective Pixels	2592 (H) × 1944 (V)
Min. illumination	Color: 0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s / NTSC: 1/30 s to 1/50,000 s
Lens	Motorized VF lens; 2.8 to 12 mm
Horizontal Field of View	27.7°to 86.8°(2.8 to 12 mm)
Lens Mount	φ14
Day & Night	ICR
Angle Adjustment	Pan:0°to340°;Tilt:0°to75°;Rotate:0°to355°
Synchronization	Internal synchronization
Video Frame Rate	2592 × 1944@20fps
HD Video Output	1HD analog output
Menu	
AGC	Support
D/N Mode	Auto/Color/BW(Black and White)
White Balance	ATW/MWB
BLC	Support
Language	English, Chinese
Functions	Brightness, Sharpness, Digital noise reduction, Mirror, Bad pixel correction, SmartIR

General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC±20% -A: 12 VDC±20% 24 VAC±20%
Power Consumption	Max. 4.5 W / A: Max. 6.5 W
Protection Level	IP67
IR Range	Up to 40 m
Communication	Up the coax,
Dimensions	Φ 145.2 mm × 124.1 mm (Φ 5.72" × 4.89")
Weight	Approx. 1600 g (3.53 lb.)

Demension

