

EV-KV8202-IM

2 Button Metal Villa Door Station

Key features

- Video intercom function
- HD video surveillance (Max. resolution 1280×720@25fps, WDR, 120° wide angle)
- Self-adaptive light supplement
- Access control function
- Activating card via local station function
- Door magnetic alarm and tamper-proof alarm function
- Noise suppression and echo cancellation
- Remote upgrade, batch setting functions



Specifications

EV-KV8202-IM		
System parameters	Processor	High-Performance Embedded SOC Processor
	Operation system	Embedded Linux Operation System
Video parameters	Camera	CMOS Low Illumination 1.3 MP HD Colorful Camera
	Video compression standard	H.264
	Resolution	1280 × 720
	Video frame rate	25 fps
Audio Parameters	Audio Input	Built-in Omnidirectional Microphone
	Audio Output	Built-in Loudspeaker
	Audio compression standard	G.711 U
	Audio compression rate	64 Kbps
	Audio Quality	Noise Suppression and Echo Cancellation
Access Control Parameters	Internal Card Reader	Built-in IC Card Reader
	Door Button	Door Button for Opening the Door
	NO/NC	Supports NO/NC Status Settings
	Door Magnetic Detection	Detects Door Magnetic Status
Light Supplement	Light Supplement Mode	IR Supplement
Network Parameters	Ethernet	10M/100M Self-Adaptive Ethernet
	Network Protocol	TCP/IP, SNMP, SIP, RTSP

Alarm Parameters	Alarm Input	Door Magnetic Alarm; Tampering Alarm
Device Interfaces	Internet Access	1 RJ45 10M/100M Self-Adaptive Ethernet Access
	RS485	1 RS485 Half-Duplex Port
	I/O Input	4
	I/O Output	1
General	Indoor Station Access Number	2
	Material	Aluminum ally
	Power Supply	Power Over Network Cable
	Consumption	≤10 W
	Working Temperature	- 40° C to + 70°C (-40° F to 158° F)
	Working Humidity	10% - 90%
	IP Protection Level	IP65
	Dimension	182 mm × 100 mm × 32.5 mm (7.17 × 3.94 × 1.28")
	Certification	FCC, CE

Typical Application

